

SHRINK-WRAPPING WITHIN REACH OF ALL: The most efficient and unexpensive shrink-wrappers around the world. Conceived and designed in order to be the best answer to the increasing demand of a simple and efficient shrink-wrapper with contained costs but great reliability. Ideal for fulfilling the various wrapping and packaging requirements of offices, banks, laboratories, archives, shops, newsagents, stationeries, bookshops, video- and music shops, storehouses, wholesalers, pasta producers, bakers, a.s.o. They can be used also to make plastic envelopes.

- "one-step[®]" system: simultaneous sealing and shrinking
- two possible working programs: sealing shrinking and sealing only.
- Traditional electronic control panel: sealing time, air temperature and time of hood closing adjustable by hand
- Hold-down solenoid (the hood remains closed up to the end of shrinking) and starting control with proximity included
- Unit-counter included
- Low maintenance
- Reduced energy consumption
- Reduced overall machine dimensions: it is not necessary a tunnel.
- Easily transportable: machine stand equipped with wheels on request
- Stand and Scrap-rewind on request

The machine works with PVC (**BLUE FILM**), polyolefin hot thermo-sealing and also shrinkable films (**GREEN FILM – GOLDEN FILM**)

Machine made according to CE rules.



SPECIFICATIONS	YS-ZB-3246	YS-ZB-4255
Power supply	230 V - 1 Ph	230 V - 1 Ph
Power required	2.1 kW	3 kW
Overall dimensions L x W	1120 x 680 mm	1270 x 780 mm
Working plate height (on stand)	920 mm	920 mm
Machine weight	71 Kg	87 kg
Sealing Area W x L	320 x 460 mm	420 x 550 mm
Altezza max prodotto	200 mm	200 mm
Impulse sealing System	bottom blade	bottom blade
Max roll dimensions DIA x W	250 x 470 mm	250 x 600 mm
Output	4-6 pc/min	4-6 pc/min

AUTOMATIC SHRINK-WRAPPING THROUGH CONTINUOUS SEALING: An automatic continuous sealer, ideal to wrap products of remarkable length such as pipes, boards, poles, skis, as this machine is equipped with a **lateral continuous sealing** system that grants a great flexibility regardless of the length of the product to be packed. The transverse sealing is made through a motorized central system that allows to do a median sealing as regards the product height and to use the right quantity of film in order to pack the product.

- It is possible to memorize 8 different working programs
- Easy product change-over and machine set-up
- Sealing controlled by a timer
- Separated electronic control for sealing-temperature and sealing-bars
- Powered infeed/outfeed conveyor
- Easy loading of film-roll and automatic film unwinding
- Powered scrap-rewinding
- Easily transportable as the machine is equipped with castors
- Ideal for "multipackage" (several products wrapped up together)
- "Kissing" conveyors to wrap small products on request
- **Center folded polyolefin hot thermo-sealing and also shrinkable films (GREEN FILM – GOLDEN FILM)** Machine made according to CE rules



SPECIFICATIONS	YS-ZB-5B
Power supply	380 V - 3 Ph
Power required	4 KW
Overall machine dimensions L x W x H	2035 x 1705 x 1200 mm
Working plate height	780 mm
Machine weight	420 kg
Minimum sealing dimensions L x W	∞ x 90 mm
Maximum sealing dimensions L x W	∞ x 420 mm
Maximum product height	200 mm
Minimum film width	150 mm
Maximum film width	650 mm
Compressed air consumption	5-6 NI/cycle
Compressed air pressure	6 bar
Output	Variable according to the product