



MP PACK



Impulse sealer

FEATURES

With excellent clarity, Impulse Sealers are the most applications and economical sealing equipment for small scale shops, home use and factories. Suitable for sealing all kinds of PE, PP, combines plastic film and aluminum plastic film. Can be wisely used in all types of industries are food, native products, sweets tea, medicine etc.



MPIS-200,300,400,500
Impulse Sealer



MPISC-200C,300C,400C
Impulse Cut Sealer

Specification						
Model	Voltage	Power	Sealing width	Sealing thickness	Size	Weight
MPIS-200	220V/110V	300W	200x2mm	0.01~0.8mm	54x35x37cm	28kg/10pcs
MPIS-300	220V/110V	400W	300x2mm	0.01~0.8mm	48x44x34cm	35kg/8pcs
MPIS-400	220V/110V	500W	400x2mm	0.01~0.8mm	56x48x20cm	30kg/5pcs
MPIS-500	220V/110V	800W	500x2mm	0.01~0.8mm	66x48x20cm	27kg/4pcs
MPISC-200C	220V/110V	300W	200x2mm	0.03~0.8mm	40x38x38cm	32kg/6pcs
MPISC-300C	220V/110V	400W	300x2mm	0.03~0.8mm	48x44x34cm	38kg/8pcs
MPISC-400C	220V/110V	500W	400x2mm	0.03~0.8mm	56x48x20cm	30kg/5pcs

Product Display

Semi-Auto Sealer



MPSAS-450,600
Semi-auto Sealer

Model	Voltage	Power	Speed	Sealing width	Sealing thickness	Size	Weight
MPSAS-450	220V/110V	600W	0~1.5 SEC	450x3mm	0.08~1mm	53x36x20cm	28kg
MPSAS-600	220V/110V	800W	0~1.5 SEC	600x3mm	0.08~1mm	68x36x20cm	27kg



Multi -Functional Film Sealer

FEATURES

This series sealer is suitable for small bags packing and adopts electronic constant temperature control system and speed adjusting transmission mechanism. It can seal films of various materials. Such as PE , PP, Aluminum foil. And can be fixed date embossing system. And the newly type (Microcomputer control) with counting device.



MPHS-900A
Dry-Ink Printing Sealer



MPHS-900W,900WL
Horizontal, Vertical Sealer

Specification								
Model	Source	Power	Sealing Speed	Sealing Width	Sealing thickness	Printing Number	Dimension (LXWXH)	Weight
MPHS-900A	220V/50Hz/110V	540W	0~12M/min	5~13mm	0.02-0.80mm	39	90x45x115cm	40kg
MPHS-900W	220V/50Hz/110V	500W	0~12M/min	5~13mm	0.02-0.80mm	39	90x45x50cm	35kg
MPHS-900WL	220V/50Hz/110V	500W	0~12M/min	5~13mm	0.02-0.80mm	39	90x45x50cm	38kg

Product Display



MPDS-200,300,400
Step Direct Heat Sealer

Step Direct Heat Sealer

Suitable for sealing with PE, PVC, PP film and aluminum foil. Widely used for sealing food, medicine, hardware or supermarket products.

Specification	
Model	Step Direct Heat Sealer
Voltage	110/220V/50 Hz
Power	270W, 350W, 450W
Sealing Speed	Manual
Sealing Width	200mmx 10mm 300mmx10mm 400mmx 10mm
Sealing thickness	0.1~1.2mm
Size	80x54x26cm
Weight	MPDS-200(6 kg) MPDS-300(28kg) MPDS-400(30kg)



Pedal Sealing Machine

FEATURES

There are two kinds of pedal sealers: impulse sealer and direct heat sealer, Impulse sealer is suitable for sealing polyvinyl chloride, polyethylene bags. Direct heat sealer is suitable for sealing cellophane, aluminum foil, copper foil, tin foil and polystyrene compound bags and heat prints the production date and expiration date in the seal. The temperature is electronically controlled and is easy to be adjusted. The temperature is stably controlled.



MPSIS-350,450,600
Step Impulse Sealer

Specification	
Model	Step Impulse Sealer
Voltage	110/220V/50 Hz
Power	500W, 600W, 800W
Sealing Speed	0~2.3 sec
Sealing Width	350mm x3mm 450mm x 2mm 450mm x 5mm
Sealing thickness	0..05~0.9mm
Size	80x54x25cm
Weight	MPSIS-350(22 kg) MPSIS-450(24kg) MPSIS-600(26kg)

Induction Sealing Machine

FEATURES

The use of plastic coated foil membranes, with or without wadding, is employed to seal plastic and glass containers for improved integrity. The seal provides a good oxygen barrier to a better shelf- life, wet and fungus-proof, also offers tamper evidence and avoids spillage, especially to chemical or solution.

The membrane is usually assembled into a screw closure, allowing the capping torque to provide good clamping, pressure to the container top. Under the influence of a "no contact" induction field the metal foils heats to melt the plastic and produce a weld. Suitable sealing materials include PET, PE, PVC, PP, PS, ABS and Glass.



Specification	
Voltage	110/220V/50 Hz
Power	600W (built in voltmeter)
Sealing Diameter	10mm-100m foil
Dimension(LxWxH)	340x280x130mm
Weight	8kg

**** Safety features include power insulation that comes with overload and power load protection.**

FEATURES

MP- DSI-1



MP PACK



Carton Sealer is suitable for carton packaging, home appliances, textiles, food, general merchandise, medicine, etc. Adopts adhesive tape to seal carton. Economical and easy to use. Compact and durable design, easy to operate top and bottom. Belt driven suit for sealing high carton. Side belts driver suit for sealing narrow carton, compact and durable design, easy to operate. High precision, lower noise and prolong the machine's life .

Cartoon Sealer



MPCS-6050
Carton Sealer

Specification	
Model	Carton Sealer (MPCS-6050)
Max (WxH)	500x600mm
Min (WxH)	150x90mm
Capacity	20M/min
The hight of worktable	500-700mm
Type of Tape	BOPP, PVC
Width of Tape	36,48,60mm
Power	220V,50Hz,300W
Dimension	170x88x142cm
Weight	120kg

Impulse Sealer



Manual Impulse Sealer (FRN-600~900)



Manual Impulse Sealer (FKR-200)- special materials for heating wire in heat jaws, the life of heating wire is much longer than other machines and it can seal even aluminum sheet or material and more by a light a material for sealing jaws, it is easy to carry in anywhere and to use in narrow place.